# HDP26-24-29SE-L024 ✓ ACTIVE

### DEUTSCH | DEUTSCH HD, DEUTSCH HDP

TE Internal #: YHDP26-24-29SEL024

Housing for Female Terminals, Wire-to-Wire, 29 Position, Sealable, Black, Wire & Cable, Power & Signal, Cable Mount (Free-Hanging),

Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings











Connector System: Wire-to-Wire

Number of Positions: 29

Connector & Housing Type: Housing for Female Terminals

Sealable: Yes

Mating Pin Diameter: 1.02 mm, 1.59 mm, 2.39 mm [ .04 in, .063 in, .094 in ]

All DEUTSCH HDP20 Housings (324)

# **Features**

# **Product Type Features**

Mixed & Hybrid Connector	Yes
Connector Shape	Circular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Contact Retainer
Configuration Features	
Blank Cavity Position	0
Connector Modification	Wide Threaded Adapter
Connector Seal Code	E Seal
Number of Positions	29



### **Electrical Characteristics**

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V

# **Body Features**

Cable Exit Angle	180°
Primary Product Color	Black

### **Contact Features**

Contact Size	Size 12, Size 16, Size 20
Contact Type	Socket
Mating Pin Diameter	1.02 mm, 1.59 mm, 2.39 mm[.04 in][.063 in][. 094 in]
Contact Current Rating (Max)	7.5 A, 13 A, 25 A

### Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Guide Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

# **Housing Features**

Llavair a Natarial	DA CE
Housing Material	PA GF

# **Dimensions**

Connector Height	49.53 mm[1.95 in]
Product Width	49.53 mm[1.95 in]
Product Length	38.3 mm[1.508 in]
Compatible Insulation Diameter Range	1.02 – 2.1 mm, 1.35 – 2.62 mm, 2.46 – 4.01 mm[.04 – .083 in][.053 – .103 in][.097 – .158 in]

# **Usage Conditions**

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	

#### Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

# **Industry Standards**



Degree of Protection	IP67
UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	1
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # CAT-H396-CH8172
DEUTSCH HDP20 Housings



TE Part # Y2428-024-24050000 BKSHL, 24SZ, BLK, ST, L024, HDP



TE Part # HD30-24BT-BK BOOT, 24SZ, ST, BLK



TE Part # HD30-24BT BOOT, 24SZ, ST, GRY



TE Part # HD30-24BT-90-BK BOOT, 24SZ, RA, BLK



TE Part # 0411-337-1205 EXT TOOL, SIZE 12, 12-14 AWG, E, ORG



TE Part # WHDS-24-1 STRAIN RELIEF, HD30, 24SZ, ST



TE Part # WHDS-24-2 STRAIN RELIEF, HD30, 24SZ, RA



TE Part # 0411-240-2005 EXT TOOL, SIZE 20, 16-22 AWG, N, RED



TE Part # 0411-336-1605 EXT TOOL, SIZE 16, 16-20 AWG, E, DRK BLU

# Also in the Series | DEUTSCH HD



Automotive Connector Caps & Covers (32)



Automotive Housings(742)



Connector Backshells(29)



Connector Seals & Cavity Plugs(10)



Connector Strain Relief(5)



Insertion & Extraction Tools(11)



Other Automotive Connector Accessories(11)



PCB Headers & Receptacles(1)

# Also in the Series | DEUTSCH HDP





Automotive Connector Caps & Covers (4)



Automotive Housings(331)



Connector Backshells(8)





Insertion & Extraction Tools(11)



Other Automotive Connector Accessories(5)

# Customers Also Bought



TE Part #WB-48SB WEDGE LOCK, 48P, PLG, BLK, DRB, B



TE Part #DRB12-48PBE-L018 REC, 48P, BLK, E, CAP, B



TE Part #2040594-4 SEAL CAP HSG 6P, AMPSEAL16 SEA



# **Documents**

# **Product Drawings**

PLG, 29P, BLK, E, WTHD, 12/16/20, S

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_YHDP26-24-29SEL024\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_YHDP26-24-29SEL024\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_YHDP26-24-29SEL024\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Female Terminals, Wire-to-Wire, 29 Position, Sealable, Black, Wire & Cable, Power & Signal, Cable Mount (Free-Hanging), Hybrid



Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

**Product Specifications** 

**Application Specification** 

English

Agency Approvals

**UL Report** 

English