732-8255-22 - ACTIVE

DEUTSCH

TE Internal #: ZPF00000000110281 Rectangular Contact Inserts, Contact Insert, Pin, 20 Pole Configuration, Wire-to-Board, 20 Position, Sealable, 5 A, Power, Signal & High Speed Data

View on TE.com >



Connectors > Rectangular Connectors > Rectangular Contact Inserts



Rectangular Connector Insert Type: Contact Insert

Contact Type: Pin

Pole Configuration: 20

Connector System: Wire-to-Board

Number of Positions: 20

Features

Product Type Features

Rectangular Connector Insert Type

Connector System

Contact Insert

Wire-to-Board

Sealable	Yes			
Connector & Contact Terminates To	Printed Circuit Board			
Configuration Features				
Number of Positions	20			
Body Features				
Primary Product Material	Composite			
Contact Features				
Contact Type	Pin			
Pole Configuration	20			
Contact Current Rating (Max)	5 A			
Mechanical Attachment				
Connector Mounting Type	Board Mount			
Housing Features				
Centerline (Pitch)	2.54 mm[.1 in]			
Usage Conditions				

C For support call+1 800 522 6752

732-8255-22

Rectangular Contact Inserts, Contact Insert, Pin, 20 Pole Configuration, Wire-to-Board, 20 Position, Sealable, 5 A, Power, Signal & High Speed Data



Operating Temperature Range	-55 – 175 °C[-67 – 347 °F]
Operation/Application	
Circuit Application	Power, Signal & High Speed Data
Packaging Features	
Packaging Quantity	1
Packaging Method	Bag
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE
	2023 (235) SVHC > Threshold:
	Pb (1.2% in alloy) Article Safe Usage Statements:

Halogen Content

Solder Process Capability

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

732-8255-22

Rectangular Contact Inserts, Contact Insert, Pin, 20 Pole Configuration, Wire-to-Board, 20 Position, Sealable, 5 A, Power, Signal & High Speed Data





Customers Also Bought



TE Part #ZPF000000000100308

TE Part #ZPF0000000000010301 9DMC-AB 40 P 02

RNF-100-1/16-9-STK	CAP200HAANA=RELAY, SPST-NO	732-8255-99	9DMC-AB 40 P 02
TE Part #ZPF00000000014278 DBC 54H 14-19 PN	TE Part #ZPF000000000203968 DMC-MD 24 B-K-S-T-A1193		

TE Part #9-1618380-3

Documents

TE Part #5052932059

Product Drawings

732-8255-22

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_ZPF00000000110281_1.2d_dxf.zip

732-8255-22

Rectangular Contact Inserts, Contact Insert, Pin, 20 Pole Configuration, Wire-to-Board, 20 Position, Sealable, 5 A, Power, Signal & High Speed Data



English

Customer View Model ENG_CVM_CVM_ZPF00000000110281_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_ZPF00000000110281_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages DEUTSCH DMC-M Series Multicavity EN4165 Connectors

English

DMC-M Series Single Module EN4165

English