



Scan the QR code and  
visit the product page



Code	<b>TK.LBQ.I0170.AEC</b>	Safety level	Informative
Dimensions (H x L)	20 mm x 60 mm (0,8" x 2,4")	Version	Inside panel
Material	PVC base with adhesive liner and protective layer	Temperatures <sup>(1)</sup>	-40°C/+95°C
Applications	Inside or outside control panels.		
Languages <sup>(2)</sup>	Inglese		
Message <sup>(3)</sup>	EN: SEE TABLE 54.1 OF UL 508A IT: VEDERE TABELLA 54.1 DELLA UL 508A		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.