



Scan the QR code and
visit the product page



| | | | |
|--------------------------|--|-----------------------------|-------------|
| Code | TK.LB.D0160S.AEC | Safety level | Danger |
| Dimensions (H x L) | 34 mm x 70 mm (1,3" x 2,8") | Version | Small |
| Material | PVC base with adhesive liner and protective layer | Temperatures ⁽¹⁾ | -40°C/+95°C |
| Applications | Machinery and control panels. Indoor and outdoor locations. | | |
| Languages ⁽²⁾ | Inglese | | |
| Message ⁽³⁾ | EN: Burn hazard. Hot surfaces. Do not touch. IT: Pericolo di ustioni. Superfici calde. Non toccare. | | |
| Certifications | c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8) | | |
| Standards of use | ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286 | | |
| Standards Construction | ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS | | |
| Standard packaging | 12 pz/pcs | | |

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.