

Features

- Local and remote continuity tester
- Lightweight design, connect alligator clips and the instrument suspends from wire/cable
- Visual (flashing bi-color LEDs) and audible (pulsating beeper) indicators
- Probe flashes green or red to indicate polarity
- Remote probe allows for one person operation
- Capable of sending signal on cable/wire runs up to 10,000 ft (3000m)
- Includes remote probe and battery

Specifications

| | |
|-----------------------------|---------------------------------------|
| Wire Verification Distance: | 10,000 feet (3000 meters) |
| Minimum Wire Size: | 26 gage |
| Power Supply: | 9V battery |
| Product Certifications: | CE |
| Visual Indicator: | Yes (Green and Red LEDs) |
| Audible Indicator: | Yes (Pulsating Beeper, approx. 85 dB) |
| Fuse: | 0.5A/250V |
| Continuity Confirmation: | Equal to or less than 2.0 K Ohms |
| Operating Temperature: | 14 to 113°F (-10 to 45°C) |
| Operating Humidity: | 0 to 85% |
| Storage Temperature: | 14 to 122°F (-10 to 50°C) |
| Dimensions: | 4.5 x 3 x 1.1 " (115 x 75 x 29mm) |
| Weight: | 3.9oz (111g) |



| Model | Description |
|--------|--------------------|
| R5300 | Continuity Tester |
| CA-52A | Soft Carrying Case |