TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

3x 12V 9AH UPS Replacement Battery Cartridge Kit for Select Best, Powerware, Liebert and Other UPS

MODEL NUMBER: RBC53



Description

These premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original manufacturer specifications and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. Compatible with a wide variety UPS brands and models. See the UPS replacement battery web page to confirm compatibility and quantity required.

Features

- Restore UPS runtime performance to its original runtime specifications
- Reusable packaging contains expired batteries for recycling center delivery
- Compatible with a variety of UPS brands

Specifications

| OVERVIEW | | |
|---------------------------------|---|--|
| UPC Code | 037332118684 | |
| BATTERY | | |
| Included Battery Set | Contains (3) 12V 9AH sealed lead acid batteries | |
| Typical Battery Lifespan | 3 - 5 years, depending on host UPS operating conditions | |
| PHYSICAL | | |
| Shipping Dimensions (hwd / in.) | 6.00 x 7.50 x 11.90 | |

Highlights

- Up to 30% longer runtime than basic replacements
- OEM certified premium batteries
- Rugged, leakproof construction
- Maintenance-free
- Wide operating temperature range

Package Includes

- 3 12V UPS replacement batteries
- Instruction manual with installation, recycling and warranty information

TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

| Shipping Dimensions (hwd / cm) | 15.24 x 19.05 x 30.23 |
|--|--|
| Shipping Weight (lbs.) | 20.00 |
| Shipping Weight (kg) | 9.07 |
| Unit Dimensions (hwd / in.) | 4.000 x 7.500 x 6.000 |
| Unit Dimensions (hwd / cm) | Jeu de 3 batteries ; chaque batterie mesure 9,4 x 6,4 x 14,9 |
| Unit Weight (lbs.) | 18.6 |
| Unit Weight (kg) | 8.44 |
| | |
| ENVIRONMENTAL | |
| Relative Humidity | 0 - 95% non-condensing |
| Operating Elevation (ft.) | 0 - 10,000 |
| Storage Elevation (ft.) | 0 - 50,000 |
| Operating Elevation (m) | 0-3000 m |
| Storage Elevation (m) | 0 - 15,200 m |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (U.S. & Canada) | 18-month limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.