

Hyperfast Diode

30 A, 400 V – 600 V

RHRG3040, RHRG3060

Description

The RHRG3040, RHRG3060 is a hyperfast diode with soft recovery characteristics. It has the half recovery time of ultrafast diodes and is silicon nitride passivated ionimplanted epitaxial planar construction. These devices are intended to be used as freewheeling/clamping diodes and diodes in a variety of switching power supplies and other power switching applications. Their low stored charge and hyperfast soft recovery minimize ringing and electrical noise in many power switching circuits reducing power loss in the switching transistors.

Features

- Hyperfast Recovery $t_{rr} = 45 \text{ ns}$ (@ $I_F = 30 \text{ A}$)
- Max Forward Voltage, $V_F = 2.1 \text{ V}$ (@ $T_C = 25^\circ\text{C}$)
- 400 V, 600 V Reverse Voltage and High Reliability
- Avalanche Energy Rated
- These Devices are Pb-Free and are RoHS Compliant


Applications

- Switching Power Supplies
- Power Switching Circuits
- General Purpose



ON Semiconductor®


www.onsemi.com



SYMBOL



MARKING DIAGRAM



| | |
|----------|-------------------------|
| \$Y | = ON Semiconductor Logo |
| &Z | = Assembly Plant Code |
| &3 | = Numeric Date Code |
| &K | = Lot Code |
| RHRG30XX | = Specific Device Code |
| XX | = 40, 60 |

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

RHRG3040, RHRG3060

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C, unless otherwise specified)

| Parameter | Symbol | RHRG3040 | RHRG3060 | Unit |
|--|---------------------------------|------------|------------|------|
| Peak Repetitive Reverse Voltage | V _{RRM} | 400 | 600 | V |
| Working Peak Reverse Voltage | V _{RWM} | 400 | 600 | V |
| DC Blocking Voltage | V _R | 400 | 600 | V |
| Average Rectified Forward Current (T _C = 120°C) | I _{F(AV)} | 30 | 30 | A |
| Repetitive Peak Surge Current (Square Wave, 20 kHz) | I _{FRM} | 70 | 70 | A |
| Non-repetitive Peak Surge Current (Halfwave, 1 Phase, 60 Hz) | I _{FSM} | 325 | 325 | A |
| Maximum Power Dissipation | P _D | 125 | 125 | W |
| Avalanche Energy (See Figures 10 and 11) | E _{AVL} | 20 | 20 | mJ |
| Operating and Storage Temperature | T _{STG, T_J} | -65 to 175 | -65 to 175 | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

PACKAGE MARKING AND ORDERING INFORMATION

| Device | Device Marking | Package | Shipping |
|----------|----------------|------------|------------|
| RHRG3040 | RHRG3040 | TO-247-2LD | 450 / Tube |
| RHRG3060 | RHRG3060 | TO-247-2LD | 450 / Tube |

ELECTRICAL SPECIFICATION (T_C = 25°C, unless otherwise specified)

| Characteristics | Symbol | Test Condition | RHRG3040 | | | RHRG3060 | | | Unit |
|--|------------------|---|----------|-----|-----|----------|-----|-----|------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| Instantaneous Forward Voltage (Pulse Width = 300 μs, Duty Cycle = 2%) | V _F | I _F = 30 A | - | - | 2.1 | - | - | 2.1 | V |
| | | I _F = 30 A, T _C = 150°C | - | - | 1.7 | - | - | 1.7 | V |
| Instantaneous Reverse Current | I _R | V _R = 400 V | - | - | 250 | - | - | - | μA |
| | | V _R = 600 V | - | - | - | - | - | 250 | μA |
| | | V _R = 400 V, T _C = 150°C | - | - | 1.0 | - | - | - | mA |
| | | V _R = 600 V, T _C = 150°C | - | - | - | - | - | 1.0 | mA |
| Reverse Recovery Time (See Figure 9) Summation of t _a + t _b | t _{rr} | I _F = 1 A, dI _F /dt = 200 A/μs | - | - | 40 | - | - | 40 | ns |
| | | I _F = 30 A, dI _F /dt = 200 A/μs | - | - | 45 | - | - | 45 | ns |
| Time to Reach Peak Reverse Current (See Figure 9) | t _a | I _F = 30 A, dI _F /dt = 200 A/μs | - | 22 | - | - | 22 | - | ns |
| Time from Peak I _{RM} to Projected Zero Crossing of I _{RM} Based on a Straight Line from Peak I _{RM} through 25% of I _{RM} (See Figure 9) | t _b | I _F = 30 A, dI _F /dt = 200 A/μs | - | 18 | - | - | 18 | - | ns |
| Reverse Recovery Charge | Q _{rr} | I _F = 30 A, dI _F /dt = 200 A/μs | - | 100 | - | - | 100 | - | nC |
| Junction Capacitance | C _J | V _R = 10 V, I _F = 0 A | - | 85 | - | - | 85 | - | pF |
| Thermal Resistance Junction to Case | R _{θJC} | | - | - | 1.2 | - | - | 1.2 | °C/W |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

RHRG3040, RHRG3060

TYPICAL PERFORMANCE CURVES




Figure 1. Forward Current vs. Forward Voltage




Figure 2. Reverse Current vs. Reverse Voltage




Figure 3. t_{rr} , t_a and t_b Curves vs. Forward Current




Figure 4. t_{rr} , t_a and t_b Curves vs. Forward Current




Figure 5. t_{rr} , t_a and t_b Curves vs. Forward Current




Figure 6. Current Derating Curve

TYPICAL PERFORMANCE CURVES (continued)




Figure 7. Junction Capacitance vs. Reverse Voltage

TEST CIRCUITS AND WAVEFORMS




Figure 8. t_{rr} Test Circuit




Figure 9. t_{rr} Waveforms and Definitions

$I_{MAX} = 1 \text{ A}$
 $L = 40 \text{ mH}$
 $R < 0.1 \Omega$
 $E_{AVL} = 1/2LI^2 [V_{R(AVL)}/(V_{R(AVL)} - V_{DD})]$
 $Q_1 = \text{IGBT (} BV_{CES} > \text{DUT } V_{R(AVL)} \text{)}$




Figure 10. Avalanche Energy Test Circuit




Figure 11. Avalanche Current and Voltage Waveforms

MECHANICAL CASE OUTLINE

PACKAGE DIMENSIONS

ON Semiconductor®



TO-247-2LD
CASE 340CL
ISSUE A


DATE 03 DEC 2019



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- B. ALL DIMENSIONS ARE IN MILLIMETERS.
- C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
- D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
- E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
 A = Assembly Location
 Y = Year
 WW = Work Week
 ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

| DIM | MILLIMETERS | | |
|-----|-------------|-------|-------|
| | MIN | NOM | MAX |
| A | 4.58 | 4.70 | 4.82 |
| A1 | 2.29 | 2.40 | 2.66 |
| A2 | 1.30 | 1.50 | 1.70 |
| b | 1.17 | 1.26 | 1.35 |
| b2 | 1.53 | 1.65 | 1.77 |
| c | 0.51 | 0.61 | 0.71 |
| D | 20.32 | 20.57 | 20.82 |
| D1 | 16.37 | 16.57 | 16.77 |
| D2 | 0.51 | 0.93 | 1.35 |
| E | 15.37 | 15.62 | 15.87 |
| E1 | 12.81 | ~ | ~ |
| E2 | 4.96 | 5.08 | 5.20 |
| e | ~ | 11.12 | ~ |
| L | 15.75 | 16.00 | 16.25 |
| L1 | 3.69 | 3.81 | 3.93 |
| ∅P | 3.51 | 3.58 | 3.65 |
| ∅P1 | 6.61 | 6.73 | 6.85 |
| Q | 5.34 | 5.46 | 5.58 |
| S | 5.34 | 5.46 | 5.58 |

| | | |
|------------------|-------------|--|
| DOCUMENT NUMBER: | 98AON13850G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | TO-247-2LD | PAGE 1 OF 1 |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales