TRIPP-LITE

External SAS Cable, 4 Lane - mini-SAS (SFF-8088) to mini-SAS (SFF-8088), 2M (6.56 ft.)

MODEL NUMBER: S524-02M



Features

- 2-meter External SAS Cable, SFF-8088 to SFF-8088
- Made with High-Performance Infiniband Cable
- Support data rates from 3.0 up to 6.0 gigabytes per second
- SFF-8088 connectors in diecast zinc housing for durability
- RoHS compliant

Specifications

| OVERVIEW | |
|---------------------------------|---------------------|
| UPC Code | 037332151995 |
| Technology | SAS |
| PHYSICAL | |
| Color | Black |
| Cable Jacket Color | Black |
| Cable Length (ft.) | 6.6 |
| Cable Length (m) | 2.01 |
| Shipping Dimensions (hwd / in.) | 5.30 x 3.90 x 0.50 |
| Shipping Dimensions (hwd / cm) | 13.46 x 9.91 x 1.27 |
| Shipping Weight (lbs.) | 0.14 |
| Shipping Weight (kg) | 0.06 |

Highlights

- High-performance 2-meter SAS external cable
- Mini-SAS SFF-8088 (iSAS) to Mini-SAS SFF-8088 (iSAS)

System Requirements

• SAS Controllers, SAS Chassis, SAS/SATA Hard Drives

Package Includes

2-Meter SAS External, SFF-8088 to SFF-8088 Cable



1000 Eaton Boulevard Cleveland, OH 44122 United States

| Unit Dimensions (hwd / in.) | 5.300 x 3.900 x 0.500 |
|----------------------------------------|---------------------------|
| CONNECTIONS | |
| CONNECTIONO | |
| Side A - Connector 1 | SFF-8088 |
| Side B - Connector 1 | SFF-8088 |
| | |
| FEATURES & SPECIFICATIONS | |
| IP68 Rated | No |
| IP20 Rated | No |
| STANDARDS & COMPLIANCE | |
| STANDARDS & COMPEIANCE | |
| Product Compliance | RoHS; EIA/ECA-310-E |
| | |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.