

## SmartRack 42U Value Series Standard-Depth Rack Enclosure Cabinet with Doors, Side, Top and Bottom Panels

MODEL NUMBER: SR2000



### Features

- Ships fully assembled
- Ships with flat, locking, front and rear doors, full-length side panels, and roof and bottom panels
- 2000 lb. (907 kg) stationary / 1100 lb. (499 kg) rolling load capacity
- Rear sets of equipment mounting rails adjust in 3/8" increments.
- Toolless accessory mounting slots for quick installation of compatible PDUs and vertical cable managers. Mounting slots are arranged in an industry-standard pattern compatible with a wide variety of accessories. Each slot can accommodate two vertical PDUs or cable managers side-by-side (four items per enclosure).
- Includes mounting hardware of 40 pieces of M6 cage nuts and 40 pieces of M6 screws
- Textured powder-coat finish for tough resistance to environmental concerns such as deployment in warehouses
- Maximum usable internal depth of 35 in. / 889 mm (front to rear rail)
- Compatibility with airflow optimization accessories, as well as cable management accessories

### Highlights

- 4 interior vertical posts with unthreaded square hole openings
- 2000 lb. (907 kg) stationary / 1100 lb. (499 kg) rolling load capacity
- Standard 24" (600 mm) width and 40" (1016 mm) depth for optimizing floor space
- Pre-installed casters and leveling feet roll through standard 7 ft. doorway
- Includes 40 pieces of M6 cage nuts and 40 pieces of M6 screws for equipment mounting

### Package Includes

- SmartRack 42U Value Series Standard-Depth Rack Enclosure Cabinet
- (1) Key sets for front / rear doors, and side panels
- (40) M6 Cage Nuts
- (40) M6 Screws
- (40) M6 Nylon Washers
- (2) Stabilizer brackets
- Owner's Manual

## Specifications

| OVERVIEW             |  |
|----------------------|--|
| UPC Code             | 037332188212                             |
| Device Compatibility | Patch Panel; Network Switch; UPS; Server |
| Rack Type            | Enclosure                                |
| PHYSICAL             |  |
| Color                | Black                                    |

|                                      |                          |
|--------------------------------------|--------------------------|
| Rack Height                          | 42U                      |
| Rack Depth                           | Standard                 |
| Maximum Device Depth (cm)            | 88.90                    |
| Maximum Device Depth (in.)           | 35                       |
| Maximum Device Depth (mm)            | 889                      |
| Minimum Device Depth (cm)            | 57.45                    |
| Minimum Device Depth (in.)           | 22.62                    |
| Minimum Device Depth (mm)            | 575                      |
| Shipping Dimensions (hwd / in.)      | 85.00 x 26.00 x 45.50    |
| Shipping Dimensions (hwd / cm)       | 215.90 x 66.04 x 115.57  |
| Shipping Weight (lbs.)               | 220.00                   |
| Shipping Weight (kg)                 | 99.79                    |
| Unit Dimensions (hwd / in.)          | 76.200 x 23.620 x 39.400 |
| Unit Dimensions (hwd / cm)           | 197.28 x 59.99 x 100     |
| Unit Weight (lbs.)                   | 169.4                    |
| Unit Weight (kg)                     | 76.84                    |
| Weight Capacity - Rolling (kg)       | 499                      |
| Weight Capacity - Rolling (lbs.)     | 1100                     |
| Weight Capacity - Stationary (kg)    | 907                      |
| Weight Capacity - Stationary (lbs.)  | 2000                     |
| Number of Vertical Mounting Rails    | 4                        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                          |
| Built-in Cable Management            | No                       |
| Extra Wide                           | No                       |
| Pre-Installed Casters                | Yes                      |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                          |
| Product Compliance                   | RoHS; EIA/ECA-310-E      |
| <b>WARRANTY &amp; SUPPORT</b>        |                          |
| Product Warranty Period (Worldwide)  | 5-year limited warranty  |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.