TRIPP-LITE

Short Riser Panels for Hot/Cold Aisle Containment System - Standard 600 mm Racks, Set of 2

MODEL NUMBER: SRCTMTR600SH




Aisle Containment System keeps hot and cool air separated for better temperature control and equipment performance in hot aisle/cold aisle configurations.

Features

Riser Panels Designed for Standard-Width 600 mm Server RacksThese SmartRack® riser panels attach to the underside of the aisle containment system's upper support beams. This is to fill the gap between the telescopic beams (SRCTMTTLBM, sold separately) and your rack cabinets. All necessary installation hardware is included. The 3U SRCTMTR600SH measures 600 millimeters (24 inches) wide and 133 millimeters (5.2 inches) high to fit 45U standard-width rack enclosures.

Aisle Containment System Manages Airflow for More Cooling EfficiencyUpon installation in your data center or server room, the modular, easy-to-assemble Aisle Containment System contains the air in a hot aisle or cold aisle, essentially creating a room within the aisle, while still keeping the aisle accessible. No costly contractor or HVAC specialist is required to install the system, which can be expanded or adapted to meet your needs. Assorted frame kits, beam kits, sliding double-door kits, roof panel kits and adapter riser panel kits (all sold separately) are necessary to assemble a hot or cold Aisle Containment System that accommodates the dimensions of your aisle and the rack enclosures within it.

Specifications



Highlights

- Riser panels designed for standard-width 600 mm rack enclosures
- Fill gap between rack cabinets and aisle containment system's telescopic beams
- Minor assembly required using the included hardware

Applications

 Provide a semi-airtight seal to prevent hot and cold air from mixing within a contained aisle in your data center or server room

System Requirements

- SRCTMTTLBM Beam Kit
- SRCTMTFRM Frame End Kit
- SRCTMTSDD Sliding Double-Door Kit
- SRCTMTCVR600 Static Roof Panel Kit

Package Includes

- (2) Riser panels
- (2) M6 x 16 screws
- (2) M6 hex nuts
- (4) M6 x 12 self-tapping screws
- (6) M6 washers
- Installation guide



1000 Eaton Boulevard Cleveland, OH 44122 United States

Shipping Dimensions (hwd / in.)	8.27 x 28.62 x 5.71
Shipping Weight (kg)	3.10
Rack Compatibility	600 mm (Standard)
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	5-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.