

## SmartOnline 120V 1.5kVA 1.2kW Double-Conversion UPS, 2U Rack/Tower, Extended Run, Pre-installed WEBCARDLX Network Interface, USB, DB9 Serial

MODEL NUMBER: **SU1500RTXL2UN**



### Description

SmartOnline® UPS systems offer high-performance power protection ideal for critical server and network equipment in data centers, computer rooms and network closets. Online, double-conversion Uninterruptible Power Supply (UPS) maintains perfectly regulated output power by continuously converting raw AC input to DC, then re-converting output back to AC. Fully regulated sine wave AC output with +/-2% voltage regulation powers network equipment continuously, even during severe brownouts and overvoltages, all without depleting UPS battery reserves. Maintains battery-derived AC output during power failures with zero transfer time. Extended runtime options available. High 95-percent efficient operation in optional economy mode saves BTU heat output and energy costs. Network management interfaces support communications via USB port, DB9 serial port and pre-installed WEBCARDLX network management interface card. The Java-free HTML5-based WEBCARDLX interface enables full remote access for site power and UPS status monitoring, configuration, control and email notifications via secure web browser, SNMP, telnet or SSH. It supports 10/100 Mbps auto-sensing for optimum communication with an Ethernet network. Optional EnviroSense2 modules (sold separately) provide a variety of environmental monitoring capabilities. Protocols supported include HTTP, HTTPS, SMTP, SNMPv1, SNMPv2, SNMPv3, telnet, SSH, FTP, DHCP and NTP. Built-in DB9 port offers both enhanced RS-232 data and basic contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and macOS. PowerAlert® UPS monitoring software is available via free download. Emergency Power Off (EPO) interface. LED display reports UPS operating mode, line power availability, battery mode operation, inverter operation and output power availability. Audible alarm with push-button momentary alarm-cancel. Programmable self-test. Fault-tolerant auto-bypass mode. Field-replaceable, hot-swappable internal batteries and external battery packs.

### Features

- SU1500RTXL2UN 1500VA / 1.5kVA / 1200W on-line, double-conversion 2U rack-mount UPS
- 120V output (120V factory preset)
- NEMA 5-15P input, 6 NEMA 5-15R
- Two switched load banks support remote reboot or programmable load shedding options
- Supports 2% output voltage regulation and zero transfer time in double conversion mode
- Economy mode option offers enhanced 95% efficiency operation, reduced power consumption and

### Highlights

- 1500VA / 1.5kVA / 1200 watt on-line double-conversion 2U rack/tower UPS
- 120V +/-2% output at 50/60Hz, High 95% efficiency economy mode option
- Expandable runtime, Hot-swap batteries; 19 in / 48.3cm installed depth
- USB, RS232, EPO and pre-installed WEBCARDLX Network Interface
- Front panel status LEDs with detailed load and battery metering
- 2 independently switchable output load banks
- NEMA 5-15P input; 5-15R outlets
- To enable the Auto Probe feature, this product requires LX firmware update 15.5.2 or later to be installed

### Package Includes

- SU1500RTXL2UN UPS with Pre-installed Network Management Card interface
- USB, DB9 & EPO Cables
- Mounting hardware for 4 post rack enclosures
- Instruction manual

lower BTU emissions

- 14 minutes runtime at 50% load (600W) and 5 minutes at 100% load (1200W) with internal batteries
- BP48V24-2U (limit 1), BP48V60RT-3U (multi-pack compatible) and BP48V27-2US (multi-pack compatible) external battery packs available (some configurations require External Battery Configuration Software)
- Intelligent battery management system extends battery life
- LED Display reports UPS operating mode, line power availability, battery mode operation, inverter status and output power availability
- Audible alarm with push-button momentary alarm-cancel
- 4-post installation hardware included, Optional 2POSTRMKITWM enables 2-post rack installation
- Single line TEL / Network surge suppression
- Electronic bypass maintains utility output during a variety of UPS fault conditions
- Network interfaces support communications via built-in USB, DB9 serial / contact-closure and pre-installed WEBCARDLX network management card
- WEBCARDLX interface allows full remote access for power monitoring, configuration, control and email notifications via secure web browser, SNMP, telnet or SSH
- Optional E2 sensors enable site monitoring of temperature, humidity and contact-closure status
- Reduce Service Calls with Auto Probe Autonomous Device Management. Auto Probe feature (Firmware 15.5.2 and greater) of the LX Platform Interface checks the connectivity status of any networked device and automatically takes one or more user-configured actions if the device fails to respond; actions include outlet reboot, set SNMP traps, SNMP OID sets, and even script execution when used in conjunction with the PowerAlert Network Shutdown Agent (PANSA)
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and macOS
- USB & Serial ports enable data-saving unattended shutdown when used with PowerAlert software, available via FREE download from [tripplite.eaton.com/products/power-alert](http://tripplite.eaton.com/products/power-alert)

## Specifications

| OVERVIEW                           |              |
|------------------------------------|--------------|
| UPC Code                           | 037332181473 |
| UPS Type                           | On-Line      |
| INPUT                              |              |
| Input Phase                        | Single-Phase |
| Rated input current (Maximum Load) | 12A          |
| Nominal Input Voltage(s) Supported | 120V AC      |
| UPS Input Connection Type          | 5-15P        |
| Input Circuit Breakers             | 20A          |
| UPS Input Cord Length (ft.)        | 10           |
| UPS Input Cord Length (m)          | 3.1          |
| Recommended Electrical Service     | 15A 120V     |
| OUTPUT                             |              |



|   |  |
|---|--|
| Battery Replacement Description                               | Hot-swappable, user replaceable batteries  |
| <b>VOLTAGE REGULATION</b>                                     |  |
| Voltage Regulation Description                                | Online, double-conversion power conditioning   |
| Overvoltage Correction  | 2% output voltage regulation during overvoltages to 150  |
| Undervoltage Correction                                       | 2% output voltage regulation during undervoltages to 80  |
| Severe Undervoltage Correction                                | 2% output voltage regulation during undervoltages to 65 (under 70% load only)  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>                  |  |
| Switches  | 2 switches control off/on power status and alarm-cancel/self-test operation. LX Platform Interface: Recessed reset switch for interface reboot and factory reset   |
| Alarm Cancel Operation  | Power-fail alarm can be silenced using alarm-cancel switch   |
| Audible Alarm   | Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions  |
| LED Indicators  | 14 LEDs indicate line power, online mode, economy/bypass mode, on-battery, overload, battery low, replace battery and fault status information; 4-LED meter displays load and battery charge levels; LED panel rotates for viewing in rack/tower formats. Network Link/Activity (Green): Flashes for network activity. Network Speed (Yellow): 10 Mbps (Flashing), 100 Mbps (On steady). LX Platform Interface Status: Normal Operation (Solid Green); Software Update (Alternating Green/Orange ~1/sec); Factory Reset (Alternating Green/Orange ~2/sec).   |
| <b>SURGE / NOISE SUPPRESSION</b>                              |  |
| UPS AC Suppression Joule Rating                               | 600  |
| UPS AC Suppression Response Time                              | Instantaneous  |
| UPS Dataline Suppression                                      | 1 line TEL/DSL (1 in / 1 out); 10/100Base T Ethernet   |
| EMI / RFI AC Noise Suppression                                | Yes  |
| <b>PHYSICAL</b>   |  |
| Primary Form Factor   | Rackmount  |
| Rack Height   | 2U   |
| Cooling Method  | Fan  |
| Included Mounting Accessory Description                       | Included 4POSTRAILKIT mounting bracket enables installation in 4 post racks from 20.5 to 36 inches (521 to 914mm)  |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount   |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount ( <a href="http://tripplite.eaton.com/2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM">2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM</a> ); 2-4 post front rail rackmount ( <a href="http://tripplite.eaton.com/Heavy-Duty-2-post-Front-Mounting-Ear-Kit-UPSHDEARKIT">UPSHDEARKIT</a> ); 4 post rackmount short-depth ( <a href="http://tripplite.eaton.com/4-Post-1U-Universal-Adjustable-Rack-Mount-Shelf-Kit-for-Wall-Mount-Racks~4POSTRAILKITWM">4-Post-1U-Universal-Adjustable-Rack-Mount-Shelf-Kit-for-Wall-Mount-Racks~4POSTRAILKITWM</a> ); Tower ( <a href="http://tripplite.eaton.com/2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems~2-9USTAND">2-9USTAND</a> ); Wallmount ( <a href="http://tripplite.eaton.com/2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM">2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM</a> ); |
| Minimum Required Rack Depth (cm)                              | 55.88  |
| Minimum Required Rack Depth (inches)                          | 22   |

|   |  |
|---|--|
| Minimum Required Rack Depth with External Battery Pack (cm)     | 66   |
| Minimum Required Rack Depth with External Battery Pack (in.)    | 26   |
| Minimum Required Rack Depth without External Battery Pack (cm)  | 56   |
| Minimum Required Rack Depth without External Battery Pack (in.) | 22   |
| Optional Mounting Accessory Notes                               | Optional <a href="//tripplite.eaton.com/2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems~2-9USTAND">2-9USTAND</a> enables upright tower UPS placement; <a href="//tripplite.eaton.com/2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM">2POSTRMKITWM</a> enables wall-mount and 2-post rackmount installation; <a href="//tripplite.eaton.com/4-Post-1U-Universal-Adjustable-Rack-Mount-Shelf-Kit-for-Wall-Mount-Racks~4POSTRAILKITWM">4POSTRAILKITWM</a> enables installation in 4-post short-depth racks from 14.5 to 23.5 inches (368 to 597mm); <a href="//tripplite.eaton.com/Heavy-Duty-2-post-Front-Mounting-Ear-Kit~UPSHDEARKIT">UPSHDEARKIT</a> enables installation in 2 or 4-post racks using front vertical rails only, without rear support |
| Primary UPS Depth (mm)  | 483  |
| Primary UPS Height (mm)   | 89   |
| Primary UPS Width (mm)  | 445  |
| Shipping Dimensions (hwd / in.)                                 | 9.10 x 20.00 x 23.40   |
| Shipping Dimensions (hwd / cm)                                  | 23.11 x 50.80 x 59.44  |
| Shipping Weight (lbs.)  | 58.00  |
| Shipping Weight (kg)  | 26.31  |
| UPS Housing Material  | Steel  |
| UPS Power Module Dimensions (hwd, cm)                           | 8.89 x 44.45 x 48.26   |
| UPS Power Module Dimensions (hwd, in.)                          | 3.5 x 17.5 x 19  |
| UPS Power Module Weight (kg)                                    | 20.00  |
| UPS Power Module Weight (lbs.)                                  | 44.1   |
| Unit Weight (lbs.)  | 45.2000  |
| Unit Weight (kg)  | 20.50  |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                     | 32° to 104°F (0° to 40°C)  |
| Storage Temperature Range                                       | 5° to 122°F (-15° to 50°C)   |
| Relative Humidity   | 0 to 95%, non-condensing   |
| AC Mode BTU / Hr. (Full Load)                                   | 612  |
| AC Economy Mode BTU / Hr. (Full Load)                           | 216  |
| AC Economy Mode Efficiency Rating (100% Load)                   | 95%  |
| Battery Mode Heat Dissipation (BTU/Hr) @ Full Load              | 667  |

| <b>COMMUNICATIONS</b>                                       |   |
|---|---|
| Network Management Cards                                    | WEBCARDLX   |
| Network Monitoring Port Description                         | Includes pre-installed WEBCARDLX Network Management Card; DB9 port supports RS232 and contact closure communications; Economy-mode setting option is available using PowerAlert software and DB9 Serial cable connection OR installed Network Management Card |
| PowerAlert Software   | For local monitoring via the UPS's built-in communication ports, download PowerAlert software at <a href="https://tripplite.eaton.com/products/power-alert">https://tripplite.eaton.com/products/power-alert</a>  |
| Communications Cable  | USB and DB9 cabling included  |
| WatchDog Compatibility                                      | Supports Watchdog application, OS and hard-reboot restart options for remote applications   |
| EPO Port  | RJ11 interface jack with 4-meter cable included. Supports normally open and normally closed EPO systems   |
| Network Management Card Description                         | Network management card included  |
| Communications Interface                                    | Contact closure; DB9 Serial; EPO (emergency power off); Pre-installed network card; Slot for SNMP/Web interface; USB (HID enabled)  |
| <b>LINE / BATTERY TRANSFER</b>                              |   |
| Transfer Time   | No transfer time (0 ms.) in online, double-conversion mode  |
| Low Voltage Transfer to Battery Power (Setpoint)            | 80V (100% load), 65V (<70% load)  |
| High Voltage Transfer to Battery Power (Setpoint)           | 150   |
| <b>FEATURES &amp; SPECIFICATIONS</b>                        |   |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported  |
| High Availability UPS Features                              | Auto Probe Monitoring and Reboot (included); Automatic inverter bypass; Hot swappable batteries; Remote management; Surge/noise protection; Zero transfer time  |
| Green Energy-Saving Features                                | High efficiency economy mode operation; Individually controllable load banks; Schedulable daily hours of economy mode operation   |
| <b>APPLICATIONS</b>   |   |
| UPS Applications  | Mission Critical Applications   |
| <b>STANDARDS &amp; COMPLIANCE</b>                           |   |
| Product Certifications                                      | CSA (Canada); NOM (Mexico); UL 1778   |
| Product Compliance  | RoHS; FCC Part 15 Class A (USA)   |
| <b>WARRANTY &amp; SUPPORT</b>                               |   |
| Product Warranty Period (Worldwide)                         | 2-year limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$250,000 &nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;&nbsp;  |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.