

- Foot & Finger Triggers
- Vacuum Pullback
- Timed & Continuous Modes



*AIR COMPRESSOR NOT INCLUDED

Electrically operated precision fluid dispenser with programmable timer.


An ideal solution for applying solder and brazing pastes, lubricants, epoxies, cyanoacrylates, anaerobics, gases, and acrylics.

Technical Specifications:

Model	205
Time Display	LED
Dispensing Time	0.001S-9.999S, 0.01S-99.99S
Size	9.75 x 8 x 3" (24.8 x 20.3 x 7.6 cm)
Weight	<3Kg
Repeat Tolerance	±0.1%
Min Volume	0.005ml
Input Voltage	110V / 60Hz
Power Consumption	<30W
Cycle Speed	> 600/Minutes
Air Input	50-100 Psi
Air Output	1-100 Psi

Tip Size Chart

Gage	Size	Color
14	.063	White
15	.054	Brown
16	.047	Dark Purple
18	.033	Dark Green
19	.027	Light Green
20	.023	Pink
21	.020	Medium Purple
22	.016	Blue
23	.013	Orange
25	.010	Red
27	.008	Lavender
30	.007	Light Gray



Scan here to learn more!

24 Walpole Park South, STE #10
Walpole, MA 02081

508-668-6044
www.sra-solder.com