

# USB-A to USB-C Cable, USB 2.0, 3A Rating, USB-IF Certified, (M/M), 13 ft. (3.96 m)

### MODEL NUMBER: U038-C13











USB-A to USB-C cable connects a smartphone or other USB-C device to the USB-A port on your computer, wall charger or car charger.

#### **Features**

USB Type-A to USB Type-C Cable Connects a USB-C Mobile Device to Your ComputerThis 13-ft. (3.96 m) USB Type-A to USB Type-C cable allows you to connect a device with a USB-C or Thunderbolt 3 port to a USB-enabled computer, charger, hard drive, hub or other peripheral for the purpose of charging, powering, syncing or transferring data. It is compatible with any device with a USB-C or Thunderbolt 3 port, including tablets, smartphones, MacBooks, Ultrabooks and Chromebooks.

**PD** Charging Cable Charges Devices and Transfers Data at USB 2.0 SpeedsThe USB Type-A to USB Type-C cable supports USB 2.0 data transfer speeds up to 480 Mbps. The Power Delivery cable also provides power output up to 3 amps (60 watts), which is more than sufficient for charging, syncing and powering compatible devices. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

**USB-IF Certification Ensures Rigorous Testing and Top-of-the-Line Performance**This USB Type-A to USB Type-C cable meets the high standards of USB-IF (USB Implementers Forum, Inc.), a non-profit organization consisting of companies that developed the USB specification. Receiving USB-IF certification means the U038-C13 meets the industry's highest environmental, mechanical and electrical standards. It operates with your USB peripherals, adapters and cables with top efficiency and safety.

#### **Highlights**

- Certified by USB-IF to ensure highest-grade construction and performance
- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient data transfers
- Power Delivery cable provides 3A (60W) power output for charging mobile devices
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- USB-A to USB-C cable compatible with all USB-A, USB-C and Thunderbolt 3 devices

#### **Applications**

- Charge and sync a USB-C mobile device from a USB-A wall charger up to 13-ft. (3.96 m) away
- Transfer data between an external hard drive or flash drive and your computer or laptop

#### **System Requirements**

- Device with a USB-C or Thunderbolt 3 port
- Device with a USB-A port

#### Package Includes

 U038-C13 USB-A to USB-C Cable (M/M), USB-IF Certified, 13 ft. (3.96 m)

## **Specifications**

| OVERVIEW   |                      |
|------------|----------------------|
| UPC Code   | 037332214928         |
| Technology | USB 2.0 (High Speed) |



| Cable Type                          | Passive                             |  |
|-------------------------------------|-------------------------------------|--|
|                                     |                                     |  |
| PHYSICAL                            |                                     |  |
| Material of Construction            | PVC                                 |  |
| Cable Jacket Color                  | Black                               |  |
| Cable Jacket Rating                 | VW-1                                |  |
| Cable Outer Diameter (OD)           | 4.4 mm                              |  |
| Cable Length (ft.)                  | 13                                  |  |
| Cable Length (m)                    | 3.96                                |  |
| Cable Length (in.)                  | 157                                 |  |
| Shipping Dimensions (hwd / in.)     | 9.00 x 7.00 x 0.50                  |  |
| Shipping Dimensions (hwd / cm)      | 22.86 x 17.78 x 1.27                |  |
| Shipping Weight (lbs.)              | 0.16                                |  |
| Shipping Weight (kg)                | 0.07                                |  |
| Unit Packaging Type                 | Polybag                             |  |
| ENVIRONMENTAL                       |                                     |  |
| Operating Temperature Range         | 14° to 140°F (-10° to 60°C)         |  |
| Storage Temperature Range           | -4° to 158°F (-20° to 70°C)         |  |
| Relative Humidity                   | 10% to 85% RH, Non-Condensing       |  |
| CONNECTIONS                         |                                     |  |
| Side A - Connector 1                | USB A (MALE)                        |  |
| Side B - Connector 1                | USB C (MALE)                        |  |
| Connector Plating                   | Nickel                              |  |
| Contact Plating                     | Gold                                |  |
| Connector Style                     | Straight                            |  |
| FEATURES & SPECIFICATIONS           |                                     |  |
| USB Specification                   | USB 2.0 (up to 480 Mbps)            |  |
| STANDARDS & COMPLIANCE              |                                     |  |
| Product Certifications              | USB-IF                              |  |
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |  |
| WARRANTY & SUPPORT                  |                                     |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty           |  |







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.