

1-Port Isolator Hospital-Grade USB Wall Charger, UL 60601-1 for Patient Care Areas, USB-A, 2.5A

MODEL NUMBER: **U280-001-W2-HG**



Safely charges a smartphone or other USB device in patient care areas or wet locations, including pool areas and bathrooms.

Features

Hospital-Grade USB Charger Certified Safe for Use in Patient Care Areas This hospital-grade USB wall charger lets you quickly and safely charge a USB mobile device within a patient care area, including patient rooms, nursing stations and treatment rooms. Recommended for smartphones, tablets, MP3 players, e-readers and other USB devices, the lightweight Isolator™ medical-grade USB charger meets UL 60601-1 specifications.

Fast Charging for Patients, Visitors or Staff in Hospitals, Clinics and Other Medical Facilities To charge your USB device, simply connect the U280-001-W2-HG to an AC outlet, and connect your device to the available USB-A port for 2.5A of charging power. The compact design allows for easy carrying in a backpack, purse, suitcase or laptop bag—ideal for visiting hours—or for connecting to an outlet located in a tight space, such as behind furniture. A mounting tab lets you permanently attach the charger to an outlet wall plate to prevent accidental disconnections.

Safe for Everyday Use in Your Home and Other “Wet” Environments This USB charger provides 80 times the protection of a standard GFCI outlet, making it a recommended charger for locations where moisture can build, including swimming pools, gym areas, laundry rooms, bathrooms, patios and kitchens. The Isolator’s special shock risk-reduction technology protects patients, staff and other users against electrical shock. The U280-001-W2-HG also protects against overcharging and overheating that can lead to fires and damaged electronics.

Specifications

OVERVIEW	
UPC Code	037332200716
Product Type	Wall Charger
Charging Form Factor	Direct Plug-In

Highlights

- Meets UL 60601-1 standards for charging mobile devices in patient care areas
- Provides 80 times the protection of a standard GFCI outlet, making it safe for wet areas
- Protects against overcharging and overheating that can start fires and damage batteries
- Convenient locking tab mounts to wall outlet for compliance and security purposes
- Great for charging in wet locations, including kitchens, pools, bathrooms and gyms

Applications

- Charge a smartphone, tablet, e-reader or other USB device within a patient care area in a hospital, clinic or doctors’ office
- Charge a USB mobile device in a wet location where moisture tends to gather, such as a bathroom, gym, pool area, laundry room or kitchen

Package Includes

- U280-001-W2-HG 1-Port Hospital-Grade USB Wall Charger, UL 60601-1

Device Compatibility	Phone; Tablet; Amazon Kindle
INPUT	
AC Power Adapter Plug(s)	NEMA 1-15P North America
AC Power Adapter Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.3A
AC Power Adapter Output Specs (V / A)	5.2V / 2.5A
Nominal Input Voltage(s) Supported	120V AC; 230V AC
Input Connection Type	NEMA 1-15P
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Voltage Compatibility (VDC)	5.2
Input Frequency	50 / 60 Hz
Input Plug Type	NEMA 1-15P (NON-POLARIZED)
Input Current	0.3A
OUTPUT	
Overload Protection	Yes
POWER	
Power Source Type	AC Adapter
Power Consumption (Watts)	13.07
Power Consumption Detail	13.07 @ Rated Load
CHARGING	
Number of Charging Ports	1
Total Charging Amps	2.5A
Total Charging Watts	12.5
Charging Method	USB
Charging Port Type	USB A (FEMALE)
Charging Ports Details	USB-A: 5V 2.5A (12.5W)
Charging Ports / Amps	3A / 2A / 1.5A
PHYSICAL	
Color	White
Material of Construction	Plastic, 94V0 PVC
Shipping Dimensions (hwd / in.)	7.50 x 5.00 x 0.50
Shipping Dimensions (hwd / cm)	19.05 x 12.70 x 1.27

Shipping Weight (lbs.)	0.15
Shipping Weight (kg)	0.07
Unit Dimensions (hwd / in.)	1.160 x 2.800 x 1.240
Unit Dimensions (hwd / cm)	2.95 x 7.1 x 3.15
Unit Weight (lbs.)	0.15
Unit Weight (kg)	0.07
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-40° to 176°F (-40° to 80°C)
Relative Humidity	0% TO 95% RH
Operating Elevation (ft.)	9842
Storage Elevation (ft.)	9842
BTUs	44.61 @ Rated Load
ESD Protection	8 kV Contact/20kV Air Discharge
CONNECTIONS	
Number of Ports	1
Side A - Connector 1	NEMA 1-15P (NON-POLARIZED)
Side B - Connector 1	USB A (FEMALE)
FEATURES & SPECIFICATIONS	
GaN Technology	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
Quick Charge Compliant	No
Driver Required	No
STANDARDS & COMPLIANCE	
External Power Supply Certifications	FCC; ETL; CSA; RoHS
Product Certifications	2MOPP; CSA (Canada); UL Listed
Product Compliance	RoHS; WEEE
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty



1000 Eaton Boulevard
Cleveland, OH 44122
United States



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.