

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

10-Port USB 3.0 SuperSpeed Hub with USB Charging

MODEL NUMBER: U360-010











Adds 10 new USB 3.0 ports to your computer, laptop, MacBook or Chromebook for connecting hard drives, smartphones and other USB devices.

Features

USB 3.0 Hub Adds up to 10 USB Devices to Your Computer, MacBook or ChromebookThis 10-port USB 3.0 hub connects directly to the USB-A port on your computer, laptop, MacBook, Ultrabook or Chromebook. It allows you to use as many as 10 USB devices, such as flash drives, external hard drives, printers, barcode scanners and digital cameras. Each USB port supports Battery Charging v1.2 (BC 1.2) standards for faster charging of mobile devices, such as Apple and Android smartphones and tablets.

Supports SuperSpeed USB 3.0 to Ensure Fast Data TransfersThe hub supports USB 3.0 SuperSpeed data transfer rates up to 5 Gbps, which is 10 times faster than USB 2.0. It is especially recommended for high-bandwidth USB 3.0 devices, such as security cameras and high-resolution webcams. Each BC 1.2 port provides up to 1.5A for charging mobile devices. When the hub is connected to AC power, it can double as a USB charger providing up to 2.4A maximum power per port (total power available to all ports depends on the external power supply).

Plug-and-Play Hub Comes Ready to Connect Right AwayThe U360-010 works with all major operating systems and requires no software or drivers to download and install. The included external power supply comes with four international plug adapters that ensure you can use the hub almost anywhere. Plus, it's backward compatible with previous USB versions, so you can also continue using older peripherals while getting maximum performance from current devices. Overcurrent and overvoltage safeguards protect your connected equipment against damage or data loss due to power surges.

Sleek and Slim Housing Designed for Everyday Workspace Use or Connecting on the GoThe compact unit is designed for convenient positioning within your reach, making USB ports accessible while not taking up much workspace. It is also slim enough to pack in your pocket, purse or laptop bag for use in a hotel, conference room or airport.

Highlights

- Adds a printer, scanner, hard drive, webcam—up to 10 USB devices—to your computer
- Supports USB 3.0 SuperSpeed rates up to 5 Gbps to ensure fast data transfers
- BC 1.2-compliant USB-A ports provide up to 5V 2.4A each for charging mobile devices
- Compact hub fits easily in your purse, backpack or laptop bag for connecting on the go
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect up to 10 USB devices to your PC, laptop, MacBook, Ultrabook or Chromebook's USB-A port
- Add easy-to-access USB ports to desktop computers that are in a cabinet, behind furniture or otherwise hard to reach
- Charge your smartphone or tablet
- Pack it in your laptop bag for quick connection of peripherals at a remote workspace or conference

System Requirements

 Compatible with all USBenabled operating systems (USB 3.0 port needed to achieve USB 3.0 speeds)

Package Includes

- U360-010 10-Port USB 3.0 SuperSpeed Hub - USB Charging
- USB-A to USB-B 3.0 cable, 3 ft.
- External power supply (Input: 100–240V, 50/60 Hz, 0.8A; Output: 5V 4A)
- (4) International plug adapters (North America, U.K., Europe, Australia)

Specifications



OVERVIEW		
UPC Code	037332221506	
Product Type	Hub	
AC Adapter	Input: 100-240V, 50/60Hz, 0.8A Max / Output: 5V, 4A	
Over Current Protection	Y	
Technology	USB; USB 2.0 (High Speed); USB 3.0 (SuperSpeed); USB 3.1 (Gen 1)	
Host Connector	USB A (MALE)	
VIDEO		
Number of Monitors Supported	0	
Extended Mode	No	
Mirror Mode	No	
DATA		
Data Ports	(10) USB A (FEMALE)	
Data Ports Details	(10) USB-A - USB 3.2 Gen 1 (5 Gbps)	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
External Power Supply Plug(s)	AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America	
Bus Powered	No	
Product Length (in.)	4.566	
Product Length (cm.)	11.59	
Product Length (ft.)	0.38	
Product Length (m.)	0.115	
POWER		
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.8A	
External Power Supply Output Specs (V / A)	5V / 4A	
External Power Supply Cord Length (ft.)	5	
External Power Supply Cord Length (m.)	1.5	
External Power Supply DC Barrel Connector Specs	OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve	
External Power Supply Certifications	CE; FCC; GS; RoHS; TUV; UL; cUL	



USER INTERFACE, ALERTS & CONTROLS LED Indicators Blue (Power) CHARGING Charging Ports USB-A: 5V 1.5A (7.5W); 2.4A Quick Charge Charging Ports / Amps 2.4A PHYSICAL Color Black Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range BTUS 11.36 BTU/Hr Power Consumption (Watts) Power Provided to Connected Device(s) CONNECTIONS Ports 10 USB 3.0 A (FEMALE)			
CHARGING Charging Ports USB-A: 5V 1.5A (7.5W); 2.4A Quick Charge Charging Ports / Amps 2.4A PHYSICAL Color Black Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Connections CONNECTIONS Ports 10 USB 3.0 A (FEMALE)	Support No USER INTERFACE, ALERTS & CONTROLS		
Charging Ports USB-A: 5V 1.5A (7.5W); 2.4A Quick Charge Charging Ports / Amps 2.4A PHYSICAL Color Black Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Cperating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
PHYSICAL Color Black Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUS 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) Lost of the A - Connector 1 USB 3.0 A (FEMALE)			
PHYSICAL Color Black Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUS 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
Color Black Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Side A - Connector 1 USB 3.0 A (FEMALE)			
Material of Construction ABS Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected DYB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Side A - Connector 1 USB 3.0 A (FEMALE)			
Unit Dimensions (hwd / cm) 2.2 x 11.6 x 6.5 Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Stide A - Connector 1 USB 3.0 A (FEMALE)			
Unit Dimensions (hwd / in.) 0.87 x 4.6 x 2.6 Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
Unit Packaging Type Box Unit Weight (kg) 0.37 Unit Weight (lbs.) 0.82 ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Side A - Connector 1 USB 3.0 A (FEMALE)			
Unit Weight (kg) Unit Weight (lbs.) Derating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Side A - Connector 1 USB 3.0 A (FEMALE)			
ENVIRONMENTAL Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Side A - Connector 1 USB 3.0 A (FEMALE)			
Operating Temperature Range 41 to 104 F (5 to 40 C) Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Side A - Connector 1 USB 3.0 A (FEMALE)			
Storage Temperature Range 32 to 149 F (0 to 65 C) Relative Humidity 20% to 80% RH, Non-Condensing BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Supply Only: 4.5A shared betw			
Relative Humidity 20% to 80% RH, Non-Condensing 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between Supply Only: 4.5			
BTUs 11.36 BTU/Hr Power Consumption (Watts) 3.3 Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
Power Consumption (Watts) Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
Power Provided to Connected Device(s) USB Only: 2.4A shared between all ports; Power Supply Only: 4.5A shared between CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
CONNECTIONS Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)			
Ports 10 Side A - Connector 1 USB 3.0 A (FEMALE)	een all ports		
Side A - Connector 1 USB 3.0 A (FEMALE)	CONNECTIONS		
(4) (40)			
Side B - Connector 1 (10) USB 3.0 A (FEMALE)			
Connector Plating Nickel			
FEATURES & SPECIFICATIONS			
USB Specification USB 1.1 (up to 12 Mbps); USB 2.0 (up to 480 Mbps); USB 3.0 (up to 5 Gbps); USB 3.0 (GB 3.1 Gen 1 (up to 5 Gbps)		
Driver Required No			
STANDARDS & COMPLIANCE			



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies