

USB-C to USB-A Adapter (M/F), 3.1 Gen 1 (5 Gbps)

MODEL NUMBER: **U428-000-F**



Connects an existing USB Type-A device or cable to the USB-C port on your smartphone, tablet, Ultrabook or computer in order to share data or charge a mobile device.

Description

The U428-000-F USB 3.1 Gen 1 Adapter connects your new USB-C smartphones, tablets, Ultrabooks and computers to your existing USB-A devices or cables in order to share data or charge a mobile device. It supports USB 3.1 Gen 1 data transfer speeds up to 5 Gbps and power output up to 3A for fast charging of mobile devices. Unlike traditional USB connectors that can be attached only one way, the reversible USB-C male connector plugs into a USB port in either direction for fast, fumble-free connection every time. Nickel-plated molded end connectors and gold-plated copper contacts ensure superior conductivity and long life. Slim form supports evolving design trends toward smaller devices. Backward compatible with USB 2.0 devices.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum

Features

Supports USB 3.1 Gen 1 Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0 Supports power output up to 3A—perfect for fast charging most mobile devices Uses same USB-A female connector as USB 3.0 devices Backward compatible with USB 2.0 devices

Reversible USB-C Male Connector Fumble-free reversible plug ensures fast, easy connection every time Strong enough for tablets, laptops and other larger platforms

Premium Construction Gold-plated copper contacts and nickel-plated molded ends provide a lifetime of heavy use and superior conductivity Slim, sleek design tailored for emerging design trends toward smaller devices

Specifications

OVERVIEW	
UPC Code	037332190826
INPUT	

Highlights

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Supports power output up to 3A for fast charging of mobile devices
- Fumble-free reversible USB-C plug on one end
- Backward compatible with USB 2.0 devices
- Slim design tailored for emerging trends toward smaller devices

System Requirements

- Device with USB-C port
- Device or cable with USB-A plug

Package Includes

- U428-000-F USB 3.1 Gen 1 (5 Gbps) Adapter, USB-C to USB-A M/F

Bus Powered	Yes
POWER	
Power Consumption (Watts)	0.10
PHYSICAL	
Color	Black
Material of Construction	PVC
Shipping Dimensions (hwd / in.)	5.90 x 3.90 x 0.50
Shipping Weight (lbs.)	0.02
Unit Dimensions (hwd / in.)	5.900 x 3.900 x 0.500
Unit Packaging Type	Polybag
Unit Weight (lbs.)	0.01
Unit Weight (kg)	0.00
ENVIRONMENTAL	
Operating Temperature Range	32° to 158°F (0° to 70°C)
Storage Temperature Range	14° to 176°F (-10° to 80°C)
Relative Humidity	10% to 90 % RH, Non-Condensing
BTUs	0.34 BTU/Hr
Power Provided to Connected Device(s)	5V 3A (15W) Output
CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	USB 3.0 A (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
UASP Support	Yes
Driver Required	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty



1000 Eaton Boulevard
Cleveland, OH 44122
United States



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.