

3-Port USB 3.2 Gen 1 Hub with LAN Port and Power Delivery, USB-C to 3x USB-A Ports and Gigabit Ethernet - White

MODEL NUMBER: U460-003-3AG-C



Adds USB-C PD charging, Gigabit Ethernet and 3 USB-A ports to the USB-C or Thunderbolt 3 port on your MacBook, Chromebook or tablet.

Features

Portable USB 3.2 Hub Turns Your Device's USB-C or Thunderbolt 3 Port into a Workstation This USB-C adapter with Power Delivery (PD) Charging expands the potential of your tablet, laptop, Chromebook, MacBook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for adding a thumb drive and other USB peripherals, powering and charging a PD Charging-compliant mobile device, and connecting to a Gigabit Ethernet network—all at the same time.

PD Charging Port Charges the Connected Chromebook, MacBook Pro or Other Device The USB-C PD charging port provides power and charging to the connected PD Charging-compliant device (such as a MacBook, Chromebook or Android smartphone). Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 3A (60W). That's sufficient wattage to fast-charge, sync and power most high-capacity devices, including the MacBook Pro. Note: USB-C PD port does not support Quick Charge (QC).

Connects USB Peripherals and Transfers Data at Fast USB 3.2 Gen 1 Speeds Three USB-A ports transfer data at speeds up to 5 Gbps, which is 10 times faster than USB 2.0, between your device and up to three USB peripherals, such as a flash drive, printer and keyboard/mouse. One dedicated USB-A port provides power output up to 5V 1.5A (5W) for quickly charging a connected device. The USB ports are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices. Note: Host must support USB OTG (On-the-Go)

Accesses a Wired Gigabit Ethernet Network The RJ45 port offers access to a Gigabit Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Connect using a UTP cable (such as N201-Series Cat6 cables, sold separately. See www.tripplite.eaton.com for details.), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Reversible USB-C Connector Attaches in Either Direction Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

Ready to Use Right from the Package, So You Can Plug and Play Immediately The plug-and-play

Highlights

- Supports USB 3.2 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Power Delivery port provides 3A (60W) power output for charging connected device
- Connects you to a wired 10/100/1000 Ethernet network when Wi-Fi is unavailable
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Save data from your computer to a USB thumb drive or external hard drive
- Access a wired Gigabit Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Connect a USB microphone/headset to record a podcast or listen to music
- Write a report using a USB keyboard with your tablet or Android phone

System Requirements

- Source device with USB-C or Thunderbolt 3 port
- Ethernet network with speeds up to 1000 Mbps

Package Includes

- U460-003-3AG-C USB 3.2 Gen 1 Portable Hub/Adapter
- Owner's manual

USB-C dock is specifically designed for use with the MacBook Pro, Google Chromebook Pixel and other laptops, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no software or drivers. It's smaller than a standard smartphone, making it easy to pack into a pocket, backpack or laptop bag for multiport convenience wherever you go.

Specifications

| OVERVIEW | |
|--|--------------------------------------|
| UPC Code | 037332193810 |
| Product Type | Hub |
| Device Compatibility | Chromebook; Computer; Laptop; Router |
| Technology | Cat5/5e; Cat6 |
| Host Connector | USB C (MALE) |
| DATA | |
| Data Ports | (3) USB A (FEMALE) |
| Data Ports Details | (3) USB-A - USB 3.2 Gen 1 (5 Gbps) |
| NETWORK | |
| Network Ports | RJ45 (FEMALE) |
| INPUT | |
| Bus Powered | Yes |
| Product Length (in.) | 6 |
| Product Length (cm.) | 15.24 |
| Product Length (ft.) | 0.5 |
| Product Length (m.) | 0.15 |
| BATTERY | |
| Battery Charging (5V/1.5A Port) | Yes |
| POWER | |
| Power Source Type | AC Adapter; Bus |
| Power Consumption (Watts) | 2.50 |
| USB Power Delivery (PD) Charging Support | Yes |
| USB Power Delivery (PD) Charging Specification | 20V/3A; 60W |
| USER INTERFACE, ALERTS & CONTROLS | |

| | |
|---------------------------------|---|
| LED Indicators | Green - Power, Orange - Activity |
| CHARGING | |
| Number of Charging Ports | 4 |
| Total Charging Watts | 60 |
| Charging Port Type | (3) USB A (FEMALE); (1) USB C (FEMALE) |
| Charging Ports | (2) USB-A: 0.9A; (1) USB-A: 5V 1.5A (7.5W); USB-C: 60W (20V 3A) Power Delivery (PD 2.0) |
| Charging Ports Details | Charge the host laptop or other PD Charging compatible device with up to 20V 3A (60W) via the PD portOne dedicated USB-A port provides up to 5V 1.5A (7.5W) of power output to quickly charge mobile devicesThe remaining two USB-A ports each provide 0.9A charging output |
| Charging Ports / Amps | (2) 0.9A; (1) 1.5A; (1) 3A |
| Compatible Devices | Chromebook; Laptop; Smartphone; Tablet |
| PHYSICAL | |
| Color | White |
| Material of Construction | ABS, PVC |
| Plug Color | White |
| Cable Jacket Color | White |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 3.9mm |
| Cable Length (ft.) | 0.36 |
| Cable Length (m) | 0.11 |
| Cable Length (in.) | 4.33 |
| Cable Length (cm) | 11 |
| Total Number of Ports | 5 |
| Shipping Dimensions (hwd / in.) | 5.51 x 0.91 x 3.94 |
| Shipping Weight (lbs.) | 0.13 |
| Unit Dimensions (hwd / in.) | 0.650 x 3.780 x 1.575 |
| Unit Dimensions (hwd / cm) | 1.65 x 9.6 x 4.0 |
| Unit Dimensions (hwd / mm) | 16.5 x 96 x 40 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.09 |
| Unit Weight (kg) | 0.04 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 113°F (0° to 45°C) |

| | |
|---------------------------------------|---|
| Storage Temperature Range | 14° to 158°F (-10° to 70°C) |
| BTUs | 8.5 BTU/Hr |
| Operating Humidity Range | 10 - 85 % RH, Non-Condensing |
| Storage Humidity Range | 5 - 90 % RH, Non-Condensing |
| Power Provided to Connected Device(s) | Up to 20V 3A (60W) Input (USB-C), 5V 1.5A (7.5W) Output USB port |
| COMMUNICATIONS | |
| Network Compatibility | 1 Gbps (Gigabit) |
| IEEE Standards Supported | 802.3; 802.3az; 802.3u; 802.3x |
| CONNECTIONS | |
| Number of Ports | 5 |
| Ports | 1 |
| Ports Detail | Connect to a wired Ethernet network at speeds up to 10/100/1000Mbps (Gigabit) |
| Side A - Connector 1 | USB C (MALE) |
| Side B - Connector 1 | (3) USB A (FEMALE) |
| Side B - Connector 2 | RJ45 (FEMALE) |
| Side B - Connector 3 | USB C (FEMALE) |
| Connector Plating | Nickel |
| Connector Style | Straight |
| FEATURES & SPECIFICATIONS | |
| USB Hub Ports | Yes |
| USB Specification | USB 2.0 (up to 480 Mbps); USB 3.2 Gen 1 (up to 5 Gbps) |
| Data Transfer Rate | 5 Gbps |
| Ethernet Support | Yes |
| UASP Support | Yes |
| Auto MDIX Support | Yes |
| Full Duplex Support | Yes |
| Suspend Mode Support | Yes |
| Remote Wakeup Support | Yes |
| Driver Required | No |
| STANDARDS & COMPLIANCE | |
| Product Compliance | CE (Europe); FCC (USA); REACH; RoHS; UKCA |
| WARRANTY & SUPPORT | |



1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|--|-------------------------|
| Product Warranty Period (Worldwide) | 3-year limited warranty |
|--|-------------------------|



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.