

# Universal Reversible USB 2.0 Cable (Reversible A to Up-Angle 5Pin Micro B M/M), 6 ft. (1.83 m)

### MODEL NUMBER: UR050-006-UPB



Universal / Reversible "A" connector allows plugging in any direction

#### **Features**

- Universal / Reversible A connector eliminates guess-work as to connector orientation
- Up-Angle Micro B connector ideal in situations where space is at a premium, and reduces stress / excessive bending on the cable
- Available in lengths up to 10-ft.
- 480Mbps USB 2.0 Data Transfer Rates
- Data and Power transference

#### **Highlights**

- Universal / Reversible A connector eliminates guesswork as to connector orientation
- Up-Angle Micro B connector ideal in situations where space is at a premium, and reduces stress / excessive bending on the cable
- Next Generation USB Digital Device Connector
- Provides both Data and Power transfers
- USB 2.0 480Mbps Transfer rates

#### **System Requirements**

 Digital devices that use the USB Micro-B Female socket

#### **Package Includes**

 6-ft. USB2.0 Universal /
Reversible A to Up-Angle Micro-USB B Device Cable (A Male to Micro-B Male)

## **Specifications**

| OVERVIEW                        |                      |  |
|---------------------------------|----------------------|--|
| UPC Code                        | 037332182449         |  |
| Technology                      | USB 2.0 (High Speed) |  |
| USB Cable Type                  | Passive              |  |
|                                 |                      |  |
| PHYSICAL                        |                      |  |
| Cable Jacket Color              | Black                |  |
| Cable Length (ft.)              | 6                    |  |
| Cable Length (m)                | 1.83                 |  |
| Shipping Dimensions (hwd / in.) | 0.10 x 5.00 x 5.00   |  |
| Shipping Dimensions (hwd / cm)  | 0.25 x 12.70 x 12.70 |  |
| Shipping Weight (lbs.)          | 0.10                 |  |





| Shipping Weight (kg)                | 0.05                         |  |
|-------------------------------------|------------------------------|--|
|                                     |                              |  |
| ENVIRONMENTAL                       |                              |  |
| Operating Temperature Range         | 14 to 122 F (-10 to 50 C)    |  |
| Storage Temperature Range           | 5 to 140 F (-15 to 60 C)     |  |
| Operating Humidity Range            | 0% to 90% RH, Non-Condensing |  |
| Storage Humidity Range              | 0% to 90% RH, Non-Condensing |  |
|                                     |                              |  |
| CONNECTIONS                         |                              |  |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)      |  |
| Side B - Connector 1                | MICRO-USB B (MALE)           |  |
|                                     |                              |  |
| WARRANTY & SUPPORT                  |                              |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty    |  |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>