



SERIES: VOF-50B | **DESCRIPTION:** AC-DC POWER SUPPLY**FEATURES**

- safety Class II design
- industry standard 2" x 4" footprint
- no-load power consumption < 0.3 W
- EN 55032 Class B radiated emissions
- 5k meters high altitude operation



| MODEL | output voltage | output current max | output power max | ripple and noise ¹ max | efficiency ² typ |
|------------|----------------|--------------------|------------------|-----------------------------------|-----------------------------|
| | (Vdc) | (A) | (W) | (mVp-p) | (%) |
| VOF-50B-12 | 12 | 4.2 | 50.4 | 120 | 87 |
| VOF-50B-15 | 15 | 3.4 | 51.0 | 150 | 88 |
| VOF-50B-24 | 24 | 2.1 | 50.4 | 240 | 89 |

Notes: 1. Measured at output within 20 MHz BW, at rated line voltage and output load, with a 10 μ F tantalum and a 0.1 μ F ceramic capacitor across the output.
 2. At 230 Vac.

PART NUMBER KEY

INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|-------------------------------|-----|------------|-------------|--------|
| voltage | | 90 | | 264 | Vac |
| frequency | | 47 | | 63 | Hz |
| current | at 115 Vac at 230 Vac | | 1.7 0.8 | | A A |
| inrush current | at 230 Vac, cold start, 25 °C | | 90 | | A |
| leakage current | at 264 Vac, 63 Hz | | | 0.25 | mA |
| no load power consumption | at 110 Vac at 230 Vac | | | 0.19 0.3 | W W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|------------------------|-----|-----|-------|-------|
| initial set point accuracy | | | ±3 | | % |
| line regulation | at full load | | | ±0.5 | % |
| load regulation | at 10% to full load | | ±1 | | % |
| adjustability | built in trim pot | | ±5 | | % |
| start-up time | at 100 Vac, full load | | | 1 | s |
| rise time | at 100 Vac, full load | | 50 | | ms |
| hold-up time | at 115 Vac, full load | 10 | | | ms |
| switching frequency | at full load | 62 | | 87 | kHz |
| temperature coefficient | | | | ±0.04 | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|-----------------------------|------------------------|-----|-----|-----|-------|
| over voltage protection | latch off | 110 | | 130 | % |
| over current protection | auto recovery | | | | |
| short circuit protection | auto recovery | | | | |
| over temperature protection | auto recovery | | | | |

SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|------------------------------------|--|-----|-------|-----|-------|
| isolation voltage | input to output | | 3,000 | | Vac |
| safety approvals | UL 62368-1, EN 62368-1, IEC 62368-1 | | | | |
| safety class | Class II | | | | |
| conducted emissions | EN 55032 Class B, FCC Class B | | | | |
| radiated emissions | EN 55032 Class B, FCC Class B | | | | |
| input current harmonics | EN 61000-3-2 Class A | | | | |
| voltage fluctuation and flicker | EN 61000-3-3 | | | | |
| ESD immunity | EN 61000-4-2, air: ±8 kV; contact: ±4 kV contact | | | | |
| radiated field immunity | EN 61000-4-3, 3 V/m | | | | |
| electrical fast transient immunity | EN 61000-4-4, ±2 kV | | | | |

Notes: 3. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

SAFETY & COMPLIANCE (CONTINUED)

| parameter | conditions/description | min | typ | max | units |
|-----------------------------|--|---------|-----|-----|-------|
| surge immunity | EN 61000-4-5, ±2 kV diff, ±4 kV com | | | | |
| conducted immunity | EN 61000-4-6, 3 Vrms | | | | |
| magnetic field immunity | EN 61000-4-8, 50 Hz, 1 A/m (rms), Class A | | | | |
| voltage dips, interruptions | EN 61000-4-11: voltage dips 30% reduction for 500 ms, Class A voltage dips >95% reduction for 10 ms, Class A voltage dips >95% reduction for 5000 ms, Class B | | | | |
| MTBF | as per MIL-HDBK-217F, 25°C, full load | 350,000 | | | hours |
| RoHS | yes | | | | |


Notes: 4. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

ENVIRONMENTAL


| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-------|-------|
| operating temperature | see derating curves | -20 | | 70 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | non-condensing | 5 | | 95 | % |
| altitude | | | | 5,000 | m |

DERATING CURVES

TEMPERATURE DERATING CURVE




INPUT VOLTAGE DERATING CURVE (at 25°C)




EFFICIENCY CURVES


EFFICIENCY VS OUTPUT LOAD VOF-50B-12 (natural convection)



EFFICIENCY VS OUTPUT LOAD VOF-50B-15 (natural convection)



EFFICIENCY CURVES (CONTINUED)



MECHANICAL


| parameter | conditions/description | min | typ | max | units |
|------------------------|---|-----|-----|-----|-------|
| dimensions | 101.6 x 50.8 x 26.6 (4.0 x 2.0 x 1.17 inch) | | | | mm |
| weight | | | 112 | | g |
| cooling | natural convection | | | | |
| CN100 input connector | CN100 mates with Jowle A3961H02-3P, crimp pin A3961T2P-2C, or Molex 09-50-3031, crimp pin 2478 series | | | | |
| CN200 output connector | CN200 mates with Jowle A3961H02-4P, crimp pin A3961T2P-2C, or Molex 09-50-3041, crimp pin 2478 series | | | | |

MECHANICAL DRAWING

units: mm
tolerance:
X≤30: ±0.25 mm
30<X≤100: ±0.35 mm
100<X≤300: ±0.50 mm
holes: ±0.20 mm

| CN100 Connector | |
|-----------------|----------|
| PIN | Function |
| 1 | AC(L) |
| 2 | NP |
| 3 | AC(N) |

| CN200 Connector | |
|-----------------|----------|
| PIN | Function |
| 1 | +V |
| 2 | +V |
| 3 | RTN |
| 4 | RTN |



REVISION HISTORY

| rev. | description | date |
|------|--|------------|
| 1.0 | initial release | 10/16/2018 |
| 1.01 | company logo updated | 11/30/2020 |
| 1.02 | over temperature protection updated | 04/06/2021 |
| 1.03 | derating and efficiency curves updated | 05/13/2021 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC

a bel group

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.