


# Optocoupler, Phototransistor Output, Low Input Current, SOP-4, Mini-Flat Package



## DESCRIPTION

The VOMA617A series has a GaAlAs infrared emitting diode, which is optically coupled to a silicon planar phototransistor detector, and is incorporated in a 4-pin mini-flat package.

It features a high current transfer ratio at low input current, low coupling capacitance, and high isolation voltage.

The coupling devices are designed for signal transmission between two electrically separated circuits, specifically for use in automotive, as well as high reliable industrial applications.

## FEATURES


- AEC-Q101 qualified
- High CTR with low input current
- SOP-4 low profile package
- High collector emitter voltage,  $V_{CEO} = 80\text{ V}$
- Isolation test voltage =  $3750\text{ V}_{RMS}$
- Low coupling capacitance
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

## APPLICATIONS

- Galvanic and noise isolation
- Signal transmission
- Hybrid / electric vehicle applications
- Battery management
- 48 V board net
- System control

## AGENCY APPROVALS

- UL1577
- cUL 1577
- DIN EN 60747-5-5 (VDE 0884-5)
- CQC GB4943.1-2011



| ORDERING INFORMATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                  |                   |                   |                   |   |   |   |   |         |                |   |   |               |   |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------|-------------------|-------------------|---|---|---|---|---------|----------------|---|---|---------------|---|---|-------------|--|--|--|--|--|--|--|--|---------|----------------|--|--|---------------|--|--|--|--|--|
| <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">V</td> <td style="text-align: center;">O</td> <td style="text-align: center;">M</td> <td style="text-align: center;">A</td> <td style="text-align: center;">6</td> <td style="text-align: center;">1</td> <td style="text-align: center;">7</td> <td style="text-align: center;">A</td> <td style="text-align: center;">-</td> <td style="text-align: center;">#</td> <td style="text-align: center;">X</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">1</td> <td style="text-align: center;">T</td> </tr> <tr> <td colspan="9" style="text-align: center;">PART NUMBER</td> <td style="text-align: center;">CTR BIN</td> <td colspan="3" style="text-align: center;">PACKAGE OPTION</td> <td colspan="2" style="text-align: center;">TAPE AND REEL</td> </tr> </table> | V                | O                 | M                 | A                 | 6 | 1 | 7 | A | -       | #              | X | 0 | 0             | 1 | T | PART NUMBER |  |  |  |  |  |  |  |  | CTR BIN | PACKAGE OPTION |  |  | TAPE AND REEL |  |  |  |  |  |
| V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | O                | M                 | A                 | 6                 | 1 | 7 | A | - | #       | X              | 0 | 0 | 1             | T |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |
| PART NUMBER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                  |                   |                   |                   |   |   |   |   | CTR BIN | PACKAGE OPTION |   |   | TAPE AND REEL |   |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |
| <b>AGENCY CERTIFIED / PACKAGE</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>CTR (%)</b>   |                   |                   |                   |   |   |   |   |         |                |   |   |               |   |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <b>5 mA</b>      |                   |                   |                   |   |   |   |   |         |                |   |   |               |   |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |
| <b>UL, cUL, VDE, CQC</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>50 to 600</b> | <b>100 to 200</b> | <b>160 to 320</b> | <b>130 to 260</b> |   |   |   |   |         |                |   |   |               |   |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |
| SOP-4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | VOMA617A-X001T   | VOMA617A-3X001T   | VOMA617A-4X001T   | VOMA617A-8X001T   |   |   |   |   |         |                |   |   |               |   |   |             |  |  |  |  |  |  |  |  |         |                |  |  |               |  |  |  |  |  |

### Note

- Additional options may be possible, please contact sales office



| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                  |            |             |                    |
|-------------------------------------------------------------------------------------------------|----------------------------------|------------|-------------|--------------------|
| PARAMETER                                                                                       | TEST CONDITION                   | SYMBOL     | VALUE       | UNIT               |
| <b>INPUT</b>                                                                                    |                                  |            |             |                    |
| Reverse voltage                                                                                 |                                  | $V_R$      | 5           | V                  |
| Power dissipation                                                                               |                                  | $P_{diss}$ | 30          | mW                 |
| Forward current                                                                                 |                                  | $I_F$      | 20          | mA                 |
| Surge forward current                                                                           | $t_p \leq 10\text{ }\mu\text{s}$ | $I_{FSM}$  | 0.5         | A                  |
| Junction temperature                                                                            |                                  | $T_j$      | 125         | $^{\circ}\text{C}$ |
| <b>OUTPUT</b>                                                                                   |                                  |            |             |                    |
| Collector emitter voltage                                                                       |                                  | $V_{CEO}$  | 80          | V                  |
| Emitter collector voltage                                                                       |                                  | $V_{ECO}$  | 7           | V                  |
| Collector current                                                                               |                                  | $I_C$      | 50          | mA                 |
| Power dissipation                                                                               |                                  | $P_{diss}$ | 150         | mW                 |
| Junction temperature                                                                            |                                  | $T_j$      | 125         | $^{\circ}\text{C}$ |
| <b>COUPLER</b>                                                                                  |                                  |            |             |                    |
| Total power dissipation                                                                         |                                  | $P_{tot}$  | 180         | mW                 |
| Storage temperature range                                                                       |                                  | $T_{stg}$  | -40 to +150 | $^{\circ}\text{C}$ |
| Ambient temperature range                                                                       |                                  | $T_{amb}$  | -40 to +110 | $^{\circ}\text{C}$ |
| Soldering temperature                                                                           | $t = 10\text{ s}$                | $T_{sld}$  | 260         | $^{\circ}\text{C}$ |

Note

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability




Fig. 1 - Power Dissipation vs. Ambient Temperature




Fig. 2 - Maximum Forward Current vs. Ambient Temperature

| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                          |             |      |      |      |               |
|----------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|-------------|------|------|------|---------------|
| PARAMETER                                                                                                | TEST CONDITION                                                           | SYMBOL      | MIN. | TYP. | MAX. | UNIT          |
| <b>INPUT</b>                                                                                             |                                                                          |             |      |      |      |               |
| Forward voltage                                                                                          | $I_F = 5\text{ mA}$                                                      | $V_F$       | -    | 1.33 | 1.5  | V             |
| Reverse current                                                                                          | $V_R = 5\text{ V}$                                                       | $I_R$       | -    | -    | 10   | $\mu\text{A}$ |
| Capacitance                                                                                              | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$                                  | $C_I$       | -    | 40   | -    | pF            |
| <b>OUTPUT</b>                                                                                            |                                                                          |             |      |      |      |               |
| Collector emitter leakage current                                                                        | $V_{CE} = 50\text{ V}$                                                   | $I_{CEO}$   | -    | 1    | 100  | nA            |
| Collector emitter breakdown voltage                                                                      | $I_C = 100\text{ }\mu\text{A}$                                           | $BV_{CEO}$  | 80   | -    | -    | V             |
| Collector emitter capacitance                                                                            | $V_{CE} = 5\text{ V}$ , $f = 1\text{ MHz}$                               | $C_{CE}$    | -    | 7    | -    | pF            |
| <b>COUPLER</b>                                                                                           |                                                                          |             |      |      |      |               |
| Collector emitter saturation voltage                                                                     | $I_F = 5\text{ mA}$ , $I_C = 1.25\text{ mA}$                             | $V_{CEsat}$ | -    | 0.25 | 0.4  | V             |
| Cut-off frequency                                                                                        | $I_F = 10\text{ mA}$ , $V_{CC} = 5\text{ V}$ , $R_L = 100\text{ }\Omega$ | $f_{CTR}$   | -    | 155  | -    | kHz           |
| Coupling capacitance                                                                                     | $f = 1\text{ MHz}$                                                       | $C_{IO}$    | -    | 1.2  | -    | pF            |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements

| <b>CURRENT TRANSFER RATIO</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                             |            |        |      |      |      |      |
|------------------------------------------------------------------------------------------------------|---------------------------------------------|------------|--------|------|------|------|------|
| PARAMETER                                                                                            | TEST CONDITION                              | PART       | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| $I_C/I_F$                                                                                            | $I_F = 5\text{ mA}$ , $V_{CE} = 5\text{ V}$ | VOMA617A   | CTR    | 50   | -    | 600  | %    |
|                                                                                                      |                                             | VOMA617A-3 | CTR    | 100  | -    | 200  | %    |
|                                                                                                      |                                             | VOMA617A-4 | CTR    | 160  | -    | 320  | %    |
|                                                                                                      |                                             | VOMA617A-8 | CTR    | 130  | -    | 260  | %    |

| <b>SWITCHING CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                             |           |      |      |      |               |
|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------|------|------|------|---------------|
| PARAMETER                                                                                               | TEST CONDITION                                                              | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
| <b>NON-SATURATED</b>                                                                                    |                                                                             |           |      |      |      |               |
| Rise time                                                                                               | $I_C = 2\text{ mA}$ , $V_{CC} = 5\text{ V}$ ,<br>$R_L = 100\text{ }\Omega$  | $t_r$     | -    | 2.3  | -    | $\mu\text{s}$ |
| Fall time                                                                                               |                                                                             | $t_f$     | -    | 3.2  | -    | $\mu\text{s}$ |
| Turn-on time                                                                                            |                                                                             | $t_{on}$  | -    | 4.9  | -    | $\mu\text{s}$ |
| Turn-off time                                                                                           |                                                                             | $t_{off}$ | -    | 3.3  | -    | $\mu\text{s}$ |
| <b>SATURATED</b>                                                                                        |                                                                             |           |      |      |      |               |
| Rise time                                                                                               | $I_F = 5\text{ mA}$ , $V_{CC} = 5\text{ V}$ ,<br>$R_L = 1.9\text{ k}\Omega$ | $t_r$     | -    | 1.1  | -    | $\mu\text{s}$ |
| Fall time                                                                                               |                                                                             | $t_f$     | -    | 6.2  | -    | $\mu\text{s}$ |
| Turn-on time                                                                                            |                                                                             | $t_{on}$  | -    | 2.0  | -    | $\mu\text{s}$ |
| Turn-off time                                                                                           |                                                                             | $t_{off}$ | -    | 10.6 | -    | $\mu\text{s}$ |




Fig. 3 - Test Circuit for Switching Characteristics




Fig. 4 - Parameter and Limit Definition

| SAFETY AND INSULATION RATINGS                |                                                                |            |                |                    |
|----------------------------------------------|----------------------------------------------------------------|------------|----------------|--------------------|
| PARAMETER                                    | TEST CONDITION                                                 | SYMBOL     | VALUE          | UNIT               |
| Climatic classification                      | According to IEC 68 part 1                                     |            | 40 / 110 / 21  |                    |
| Pollution degree                             | According to DIN VDE 0109                                      |            | 2              |                    |
| Comparative tracking index                   | Insulation group IIIa                                          | CTI        | 175            |                    |
| Maximum rated withstanding isolation voltage | According to UL1577, t = 1 min                                 | $V_{ISO}$  | 3750           | $V_{RMS}$          |
| Maximum transient isolation voltage          | According to DIN EN 60747-5-5                                  | $V_{IOTM}$ | 6000           | $V_{peak}$         |
| Maximum repetitive peak isolation voltage    | According to DIN EN 60747-5-5                                  | $V_{IORM}$ | 707            | $V_{peak}$         |
| Isolation resistance                         | $T_{amb} = 25\text{ }^{\circ}\text{C}, V_{IO} = 500\text{ V}$  | $R_{IO}$   | $\geq 10^{12}$ | $\Omega$           |
|                                              | $T_{amb} = 100\text{ }^{\circ}\text{C}, V_{IO} = 500\text{ V}$ | $R_{IO}$   | $\geq 10^{11}$ | $\Omega$           |
|                                              | $T_{amb} = T_S, V_{IO} = 500\text{ V}$                         | $R_{IO}$   | $\geq 10^9$    | $\Omega$           |
| Output safety power                          |                                                                | $P_{SO}$   | 550            | mW                 |
| Input safety current                         |                                                                | $I_{SI}$   | 180            | mA                 |
| Input safety temperature                     |                                                                | $T_S$      | 175            | $^{\circ}\text{C}$ |
| Creepage distance                            |                                                                |            | $\geq 5$       | mm                 |
| Clearance distance                           |                                                                |            | $\geq 5$       | mm                 |

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits




Fig. 5 - Input Safety Current vs. Ambient Temperature




Fig. 6 - Output Safety Power vs. Ambient Temperature

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 7 - Forward Current vs. Forward Voltage




Fig. 10 - Collector Current vs. Collector Emitter Voltage (sat.)




Fig. 8 - Collector Current vs. Collector Emitter Voltage (non-sat.)




Fig. 11 - Normalized CTR (non-sat.) vs. Ambient Temperature




Fig. 9 - Leakage Current vs. Ambient Temperature




Fig. 12 - Normalized CTR (sat.) vs. Ambient Temperature




Fig. 13 - Normalized CTR (non-sat.) vs. Forward Current




Fig. 16 - Cut-Off Frequency vs. Collector Current




Fig. 14 - Normalized CTR (sat.) vs. Forward Current




Fig. 17 - Switching Time vs. Load Resistance




Fig. 15 - Phase Angle vs. Frequency

**PACKAGE DIMENSIONS** (in millimeters)





Fig. 18 - Package Drawing

**PACKAGE MARKING** (example of VOMA617A-3X001T)



**Notes**

- XXXX = LMC (lot marking code)
- Option 1 is reflected with letter "X"
- Tape and reel suffix (T) is not part of the package marking

**PACKAGING INFORMATION** (in millimeters)





Fig. 19 - Tape and Reel Shipping Medium (EIA-481, revision A, and IEC 60286)



**Note**

- Cummulative tolerance of 10 spocket holes is 0.20 mm


Fig. 20 - Tape and Reel Packing

| TAPE AND REEL PACKING |            |
|-----------------------|------------|
| TYPE                  | UNITS/REEL |
| SOP-4                 | 2000       |





**SOLDER PROFILES**



19841

Fig. 21 - Lead (Pb)-free Reflow Solder Profile According to J-STD-020 for SMD Devices

**HANDLING AND STORAGE CONDITIONS**

ESD level: HBM class 2

Floor life: 168 h

Conditions:  $T_{amb} < 30\text{ °C}$ ,  $RH \leq 60\%$

Moisture sensitivity level 3, according to J-STD-020



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.