

WXSf 120

Product no.: T0051391199



Benefits

- ➔ ➤ Efficient, single-handed soldering
- Precise operation for highest quality work
- Nonstick coating inside solder feed tube (no flux adhesion; save on maintenance costs)
- Integrated start / stop / standby functions conserves energy and extends the service life of the unit
- Amount of solder can be pre-set for efficient use. Feed motion is adjustable from 1 mm/s to 27.5 mm/s (0.04 in./s to 1.08 in.s)
- Timer mode: a defined amount of solder is applied each time the finger switch is depressed (LED on)
- Pulse mode: the solder wire is continuously delivered as long as the switch is pressed (LED off)
- Compatible with Weller WX series soldering and rework base stations (sold separately)
- Compatible with 0.5mm, 0.8mm, and 1.0 mm solder wire diameters
- Consists of WXSf120 solder feeder unit, XTB (2.4 mm) soldering tip, 120W soldering iron with integrated solder feeder





Technical Data

| | |
|---|---------------------------------|
| Active Tip heating element technology | --- |
| Power Response heating element technology | on |
| Silver Line heating element technology | --- |
| Voltage | 24 V AC |
| Power | 120 W (126 W) |
| Tip range | XT |
| Supply unit | WX 1, WX 2, WXD 2, WXA 2, WXR 3 |
| WX-compatible | on |
| Temperature range °C | 100 - 450 |
| Temperature range °F | 200 - 850 |
| Heating time | 14 |
| Safety rest | --- |
| Safety rest (optional) | --- |
| Barrel | T0058763731 |
| Integrated direct extraction | --- |